

Reversible ketone hydrogenation and dehydrogenation for aqueous organic redox flow batteries

Ruozhu Feng, Xin Zhang, Vijayakumar Murugesan, Aaron Hollas, Ying Chen, Yuyan Shao, Eric Walter, Nadeesha P. N. Wellala, Litao Yan, Kevin M. Rosso, Wei Wang

Science, 2021, 372, 836.


DOE-OE Peer Review 2021 Virtual October 2021







Redox Flow Batteries (RFB)



Nat. Rev. Mater 2016, 2, 16080.

Technology suitable for

Long Duration Energy Storage

Modular design

- Decoupled energy storage and power generation
- ♦ Versatile application

High safety

- ♦ Spatial separation of reactive materials
- water based electrolyte
- ♦ Easy thermal management
- Battery health monitoring

Easy material recycling after service life


Consumption vs. Investment



From Vanadium evolving into Organics


Vanadium Redox Flow Battery (VRB)

- Current state-of-the-art, highly studied
- High material capital cost



> Benefits of Organics

- ♦ Potentially lower material cost on large scale
- Tunability of material and supporting electrolyte
- ♦ Candidates with 2e⁻ redox events



New materials development to


- drive down cost
- improve performance



Common examples of active material


Positive electrolyte

Negative electrolyte



Limited library

Top Challenge Material Stability






- 2e redox event
- ✓ High energy density
- √ Fast kinetics





Fluorenone (FL) core structure

Highly stable FL ring structure Even at charged state




FL dianion in THF-d8 reflux at 66°C for half year

Tetrahedron Letters 1999, 40, 7347-7350.


FL/FL radical anion: 1e redox chemistry in RFB

Nonaqueous system



Angew. Chem. Int. Ed. 2015, 54, 8684.


Aqueous system




ECS Trans. 2019, 89, 49-59.



Ketone hydrogenation



DFT calculation of oxidation potential on dianion and alcohol



- ***** Electrochemical irreversible
- Protonation leads to loss of reversibility




Design strategy


Reversibility

- ➤ Electron Withdrawing Group (EWG) for acidic C-H
- > Re-generate anionic species

Solubility Carnelley's rule











Battery performance at room temperature







- > 4-month continuous cycling at constant current
- > 0.02%/day observed battery capacity decay (minor de-sulfonation)
- > 90% Energy efficiency (EE)
- > Reasonable rate on demonstrated benchtop scale



Battery performance at elevated temperature






- > Stable cycling at elevated temperature (50 °C) and ambient environment
- > 70% Energy efficiency (EE) at 100mA/cm2 on benchtop cell (10cm2 cell)
- > Faster decay observed due to crossover and other issues




Observe unconventional cycling behavior

Concentration dependent discharge reversibility




pKa dependent discharge reversibility



Validate EWGs needed to support discharge



Apply unconventional redox mechanism



- > electrochemical process coupled with chemical reaction
 - **❖** First reported redox mechanism that couple chemical reaction for RFB
- > Deprotonation of the C-H is vital to initiate reversible discharge
 - ❖ First reported strategy that activate redox in-active material



Summary

High energy density FL based anolyte material developed with 2e redox chemistry

Summary

- → High stability FL based flow battery demonstrated for continuous 4-month cycling
- New redox mechanism discovered for flow battery; potential library expanded

"These FL anolytes not only display exceptional energy storage performance but also exhibit an unprecedented two-electron storage mechanism."

Recognition from the field

T. Leo Liu, etc. *Science*, **2021**, *372*, 788.

"The study by Feng et al. is significant in this context because it not only introduces an entirely new class of organic molecule as a candidate in aqueous RFBs, but also offers a strategy for activating redox activity in a molecule that is natively redox-inactive."

David G. Kwabi, *Joule*, **2021**, *5*, 1636-1638.

Future Direction

Achieve higher power density /current density



Acknowledgements

- ► US DOE-Office of Electricity under Dr. Imre Gyuk
- Pacific Northwest National Laboratory is a multi-program national laboratory operated by Battelle Memorial Institute for the U.S. Department of Energy.

Thank You For Your Attention Questions?
Ruozhu.feng@pnnl.gov